

SE-11 SOLAR WATER HEATER CONTROLLER



FOB Shanghai Price: USD9.9/pcs

Automatic Monitor

Major Technical Indications

Dimension: 155×105×35mm

Packing Box: 340×125×65mm

- 1. Power supply: 220VAC Power consumption: $\leq 4.5W$**
- 2. Accuracy of temperature measuring: $\pm 2^{\circ}C$**
- 3. Range of temperature measuring: $0^{\circ}C-99^{\circ}C$**
- 4. Water level classification: Five classes display**
- 5. Electromagnetic valve parameter: DC12V, pressurized or un-pressurized valve are available for selection.**

Operating pressure of pressurized valve: 0.02Mpa-0.8Mpa, suitable for supply water directly.

Operating pressure of un-pressurized valve: 0.0Mpa, suitable for water-tank supply or low hydraulic-pressure supply.

Main Functions:

- | | | |
|---|--|----------------------------------|
| *Power on self-test | *Water temperature preset | *Water level indication |
| *Water level set | *Water shortage alarming | *Water shortage loading |
| *Manual water loading | *Temperature-controlled loading | *Compulsive water loading |
| *Water quality set | *Automatic pressurization | *Failure instruction |
| *Low water pressure loading | *Pipe warm preservation | *Auto leakage prevention |
| *High-temperature explosion protection | | |